

Compuprint 4247-L03 Multiform Printer

Compuprint 4247-L03



Industrial

Reliability and forms flexibility for low- and mid-volume supply chain output, office applications and demand document retail environments

High reliability—Low cost of ownership

Designed to meet low- to mid-volume output requirements, the Compuprint 4247-L03 can provide reliable supply chain printing at an attractive total cost of ownership. A low-cost alternative to laser technology, the Compuprint 4247-L03 can deliver broad forms flexibility, support for wide-format printing and the convenience of remote printer management. The optional integrated Ethernet attachment allows you to integrate this printer easily into a variety of network environments.

Focus on performance and uptime

Reliability and consistent performance are critical to supply chain success. The heavy-duty construction and fast speed of the Compuprint 4247-L03 make it suitable for office-to-warehouse environments that require reliable and efficient point-of-need printing. The remote printer management software, which is included with the optional Ethernet feature, eases setup and minimizes output interruptions. This software enables remote configuration of multiple printers via the user-friendly graphical interface and proactive printer monitoring to provide real-time printer status.

Satisfy output and operator requirements

The Compuprint 4247-L03 provides convenient front-loading primary and secondary paper paths capable of supporting two applications on one printer. The straight-through paper path design can assure reliable forms feeding while enabling the use of many paper types of varying thicknesses.

HIGHLIGHTS

- Prints up to 720 characters per second for fast, reliable job completion¹
- Easy to use operator panel and overlays that support ease of use across the Compuprint 4247 family
- Rugged design for superior durability in rigorous environments
- Powerful remote printer management
- Automatic forms loading and thickness adjustment
- Ease integration with available connectivity—integrated Ethernet, USB 2.0, RS232 serial, and parallel interfaces



Operators will appreciate the multilingual LCD display and intuitive, new and improved easy-to-use operator panel. The optional matching printer stand completes the solution and simplifies setup and location choices.

Rely on Compuprint, supplies and experience

In addition to the standard warranty, Compuprint offers comprehensive service and support that extends your coverage. For more information contact local distributor or visit the web at:

www.compuprint.com

Compuprint 4247-L03 Multi-Form Printers at a glance

Max. Print Speed¹ (at 10cpi)	Draft mode 720 cps Best Draft mode 400 cps NLO mode 262 cps LQ mode 133 cps
Print options	13.6"/345.44 mm maximum print line Vertical spacing: 6 or 8 lpi selectable from operator panel for text 3, 4, 6, 8 or 9 lpi selectable under program control for text 1/144" increments under program control available for graphics Horizontal spacing: 10, 12, 15, 16.7, 17.1 and 20 cpi, 10 cpi in Fast draft mode Proportional spacing is available in DP text and NLO mode
Bar Codes	UPC-A, UPC-E, UPC-2, UPC-5, EAN-8, EAN-13, Code 3 of 9, Code 128, Interleaved 2 of 5, Industrial 2 of 5, Codabar, MSI and Matrix 2 of 5
Paper handling	Support for two continuous forms paths Dual front tractors Paper parking, switching and linking Automatic forms loading and thickness adjustment
Paper Sizes	Continuous forms: 3" to 17" (76 mm to 432 mm) width, 3" to 24" (76 mm to 610 mm) length
Emulations	IBM Proprinter: XL24 /XL24 AGM, 2391 Personal Printer. Epson ESC/P LQ series, ANSI X3.64 and CPG Native Commands Set Epson LK1600 (for DBCS model)
Interfaces	Centronics Parallel, Serial (RS-232C), USB 2.0, Ethernet 10/100 BaseT
Input Buffer	up to 128Kb
Drivers	Windows ® 2000, XP, VISTA, Win7 (32 and 64 bit)
Physical characteristics	WxDxH: 26.4" x 17.7" x 12.6" (670 mm x 450 mm x 320 mm) 46.3 lb./21 kg (weight)
Environmental conditions	Relative Humidity: 40% to 60% (non condensing), RH Temperature: 50° to 104°F (10° to 40°C) Operating Relative Humidity: 5% to 95% (non condensing), RH Temperature: -31°F to 149°F (-35° to 65°C) Storage Acoustics Printing: 53.9 to 59.7 dBA depending on configuration

Compuprint 4247-L03 Multi-Form Printers at a glance

Power Voltage	90 to 244 Vac
Power Frequency	50/60 Hz
Power Consumption	Maximum, 240 Watts, Typical 160 Watts, Power Saver Mode 22 Watts
Heat Output	154 W typical (526 BTU/hr), 22 W Idle (75 BTU/hr)
Workload²	50.000 pages per month
Throughput	610 pages per hour (ECMA 132)
Rated Printhead Life	800 million draft characters
Consumables³	15 million characters black inked ribbon
Reliability MTBF	20.000 hours at 25% D.C.

ENDNOTES

- ¹ Exact speed varies depending on document complexity, system configuration, software application, driver and printer state.
- ² The maximum workload is calculated at rated duty cycle (4 hours a day for 22 days month)
- ³ Ribbon life depends on many factors, including printer condition, machine settings, paper quality and bar code. For optimum printer performance use only genuine consumables Compuprint.
-

Ordering Information

Printer

4247-L03 Multiform Printer 45U2382-C

Controller Interface (initial)

4247-L03 SBCS Controller with Parallel/Serial/USB 45U2368-C

4247-L03 SBCS Controller with Parallel/Ethernet 10/100 45U2369-C

4247-L03 DBCS Controller with Parallel/Serial/USB 45U2370-C

4247-L03 DBCS Controller with Parallel/Ethernet 10/100 45U2371-C

Options Finishing

4247-L03 Front second tractor - 4 pin 44D8975-C

4247-L03 Printer Stand 44D8973-C

Supplies

4247-L03 Black ribbon (15MC) 41U2235-C

© Copyright Compuprint srl Printed
In Italy 2011

All rights reserved. All other
company and product names are
Trademarks or registered
trademarks of their respective
owners.

Subject to change without notice.

Version: 1.2- 04.10.2012

MAN-10307.00.00



Compuprint Commercial Contacts

Italy: Tel: +39 0119892 133

Fax :+39 011 9974432

Email: sales@compuprint.com

Internet: www.compuprint.com

