

ST™ MACHINE FILM

Ideal For Demanding Pallet Loads!

- ***Superior three-layer blown, co-extruded Machine Film.***
- ***Proprietary Metallocene resin formulation, with a true one-sided cling.***
- ***Formulated to exceed prestretch levels of 250 to 300%.***
- ***No migrating tackifier which eliminates telescoping and any cling residue.***
- ***Recommended for B and C type loads.***
- ***Outstanding tear and puncture resistance.***



ST – High Performance 3-Layer Blown Machine Grade Stretch Film							
Part Number	Gauge	Micron	Roll Width in Inches	Feet/ Roll	#s/ Roll	Rolls/ Skid	Skids/ TLD
ST-2027	106	27	19.7	4,500	37.57	40	27
ST-2020	79	20	19.7	6,000	37.10	40	28
ST-2018	71	18	19.7	6,500	36.17	40	28
ST-2016	63	16	19.7	7,500	37.10	40	28
ST-3027	106	27	29.5	4,500	56.35	20	36
ST-3020	79	20	29.5	6,000	55.65	20	36
ST-3018	71	18	29.5	6,500	54.26	20	38
ST-3016	63	16	29.5	7,500	55.65	20	36

ITW Muller
An Illinois Tool Works Company